## Amendments to the Claims:

A listing of the entire set of pending claims (including amendments to the claims, if any) is submitted herewith per 37 CFR 1.121. This listing of claims will replace all prior versions, and listings, of claims in the application.

## **Listing of Claims:**

- 1. (Currently amended) A processing system arranged for execution of a set of instructions under control of a program counter (PC), the processing system comprising:
- [[-]] an execution unit (EX1, EX2);
- [[-]] a first register file-(RF1, RF2) for storing arranged to store data, the first register file being accessible by the execution unit;
- [[-]] a program memory (PM) for storingarranged to store the set of instructions;
- [[-]] a second register file (RF3) for storingarranged to store a value of the program counter, the second register file being accessible by the execution unit-(EX2),

and wherein the execution unit (EX2) is arranged to conditionally execute a dedicated instruction for writing a value of the program counter into the second register file to initiate a delayed branching operation in which non-branch operations are executed prior to a branching operation.

2. (Currently amended) A processing system according to claim 1, wherein the processing system further comprises a controller (CTR);

Page 3 of 10

Appl. No. 10/554,621 Final Amendment and/or Response Reply to final Office action of 21 February 2007

wherein the second register file is accessible by the controller; and

wherein the controller is arranged to use the value of the program counter stored in the second register file, to fetch an instruction from the program memory.

- 3. (Original) A processing system according to claim 2, wherein the controller is further arranged to increment the value of the program counter and to write the incremented value of the program counter into the second register file.
- 4. (Original) A processing system according to claim 3, wherein the processing system is further arranged to write either the value of the program counter incremented by the controller into the second register file, or to write the value of the program counter produced by the execution unit into the second register file, depending on the evaluation of a branch condition.
- 5. (Currently amended) A processing system according to claim 1, characterized in that wherein the execution unit (EX2) is further arranged to evaluate a branch condition and subsequently use the result of the evaluation as a guard (GU2) to conditionally execute a first dedicated instruction for writing a value of the program counter into the second register file.
- 6. (Currently amended) A processing system according to claim 1, characterized

in thatwherein the execution unit (EX2)-is further arranged to execute a second dedicated instruction;

the second dedicated instruction having at least a first argument and a second argument, the second argument being a value of the program counter;

wherein the second dedicated instruction is arranged to write the value of the program counter into the second register file, depending on the value of the first argument.

7.	(Currently amended)	A processing system-according to claim 1 arranged for
execution of a set of instructions under control of a program counter, the processing system		
comprising:		
	an execution unit;	
	a first register file arrange	d to store data, the first register file being accessible by the
execution unit;		
***************************************	a program memory arrang	ed to store the set of instructions;
	a second register file arra	inged to store a value of the program counter, the second
register file being accessible by the execution unit.		
	wherein the execution	unit is arranged to conditionally execute a dedicated
instruction for writing a value of the program counter into the second register file, and		
	_wherein the processing s	system is further arranged to execute a plurality of said
dedicated instructions in parallel, and wherein during the compilation step it is guaranteed		
that only one instruction of the plurality of dedicated instructions is conditionally executed.		

- 8. (Currently amended) A processing system according to claim 1, characterized in thatwherein the processing system is a data-stationary Very Large Instruction Word (VLIW) processor, wherein the execution unit is a plurality of execution units and wherein the VLIW processor further comprises:
- [[-]]\_—a plurality of execution units (EX1, EX2);
- [[-]] a communication device (CN) for couplingarranged to couple the execution units and the first register file.
- 9. (Currently amended) A processing system according to claim 1, characterized in that wherein the processing system is a time-stationary Very Large Instruction Word (VLIW) processor, wherein the execution unit is a plurality of execution units and wherein the VLIW processor further comprises:
- [[-]]\_ a plurality of execution units (EX1, EX2);
- [[-]] a communication device (CN) for couplingarranged to couple the execution units and the first register file;

and wherein the VLIW processor is further arranged to dynamically control the transfer of result data from an execution unit of the plurality of execution units to the first register file and the second register file, based on control information derived from the set of instructions.

- 10. (Currently amended) A VLIW processor according to claim 8, <del>characterized in thatwherein</del> the register file is a distributed register file (RF1, RF2).
- 11. (Currently amended) A VLIW processor according to claim 8, characterized in that wherein the communication device is a partially connected communication network (CN).
- 12. (Currently amended) A method for executing a set of instructions by a processing system, wherein the processing system comprises:
- [[-]] an execution unit (EX1, EX2);
- [[-]] a first register file (RF1, RF2) for storing data, wherein the first register file is accessible by the execution unit;
- [[-]] a program memory (PM)-for storing the set of instructions;
- [[-]] a second register file (RF3) for storing the program counter, wherein the second register file is accessible by the execution unit,
- [[-]] and wherein the method comprises the following steps:

executing a dedicated instruction for writing a value of the program counter into the second register file;

using the value of the program counter for fetching an instruction from the program memory;

executing said instruction; and

Page 7 of 10

initiating a delayed branching operation in which non-branch operations are executed prior to executing the dedicated instruction.

13. (Currently amended) A compiler program product stored on a computer readable medium being arranged for implementing all steps of the method for programming a processing system according to claim 12, when said compiler program product is run executable on a computer system.